

# AC25CBV ♦ AC25QL



## Premium manual pallet truck 2500 kg maximum load capacity

### FEATURES

- Robust design
- 3 mm thick frame
- German Wagner powder coating
- Ø 200 mm steering wheels
- CBV: rubber steering wheels, polyurethane rollers
- German pump seals
- Galvanized body pump
- Ergonomic handle
- 6204 2RS sealed bearings
- 200° handle rotation

**PUMP: 3-YEAR WARRANTY**  
**CHASSIS: 5-YEAR WARRANTY**



AC25QL ♦ RAL 2002

#### Available in option

- Axle, bearings, stainless steel chains
- Extreme temperature bearings
- Extreme cold oil
- Foot pedal
- Safety guard
- Handbrake, foot brake, deadman switch
- Polyurethane and/or polyamide wheels and rollers
- Anti-static wheels

**QUICK LIFT TECHNOLOGY**  
**UP TO 150 KG IN ONLY**  
**6 PUMP STROKES**



AC25CBVROUGE ♦ RAL 3002

AC25CBV ♦ RAL 2002

AC25CBVORANGE ♦ RAL 2004

AC25CBVERT ♦ RAL 6018

AC25CBVJAUNE ♦ RAL 1003

AC25CBVBLEU ♦ RAL 5010

AC25CBVGRIS ♦ RAL 9006

Entry roller ————— Exit roller



#### Wheel options

- CGV** ♦ rubber steering wheels, polyurethane single rollers
- VBV** ♦ polyurethane steering wheels, polyurethane tandem rollers
- VGV** ♦ polyurethane steering wheels, polyurethane single rollers
- NBN** ♦ polyamide steering wheels, polyamide tandem rollers
- NGN** ♦ polyamide steering wheels, polyamide single rollers

Specifications	Product Reference ♦ Model		AC25CBV	AC25QL
	Capacity	kg	2500	2500
Weight	Weight	kg	74	74
Wheels	Steering wheel	mm	Ø 200x50	Ø 200x50
Dimensions	Fork raised height	mm	200	200
	Fork lowered height	mm	85	85
	Fork length	mm	1150	1150
	Width across forks	mm	540	540
Performance	Pump strokes		12	6