

# SAC200



Graphite  
SERIES



## Double cylinder hand truck with retractable stand 200 kg

### FEATURES

- Suitable for two cylinders up to Ø 250 mm
- Effortless and functional handling
- Excellent stability thanks to a double retractable stand
- Includes a securing chain



**DOUBLE SEALED BALL BEARINGS**

**SCRATCH-RESISTANT HAMMERED FINISH**

**4 MODELS AVAILABLE**



**RG**

High-quality pneumatic wheel with high density PP body



**RSB**

High-quality non-marking silent blue elastic rubber wheel



**RSN**

High-quality silent black elastic rubber wheel



**RINC**

High-quality puncture-proof non-marking silent foam wheel



Ø 250 mm cylinders



| Model                       |    | SAC200-RG                  | SAC200-RSB                                   | SAC200-RSN                  | SAC200-RINC                                  |
|-----------------------------|----|----------------------------|--|-----------------------------|--|
| Load capacity               | kg | 200                        | 200  | 200                         | 200  |
| Cylinder max. diameter      | mm | Ø 250                      | Ø 250  | Ø 250                       | Ø 250  |
| Dimensions unfolded (LxDxH) | mm | 730x980x1050               | 730x980x1050                                 | 730x980x1050                | 730x980x1050                                 |
| Dimensions folded (LxDxH)   | mm | 730x430x1180               | 730x430x1180                                 | 730x430x1180                | 730x430x1180                                 |
| Nose-plate dimensions (LxD) | mm | 580x280                    | 580x280                                      | 580x280                     | 580x280                                      |
| Type of wheel tires         |    | pneumatic                  | non-marking silent blue elastic rubber wheel | silent black elastic rubber | non-marking silent puncture-proof foam wheel |
| Type of wheel hub           |    | high density PP            | polyamide 6                                  | polyamide 6                 | high density PP                              |
| Type of bearings            |    | double sealed ball bearing | double sealed ball bearing                   | double sealed ball bearing  | double sealed ball bearing                   |
| Wheels                      | mm | Ø 260                      | Ø 250  | Ø 250                       | Ø 260  |
| Weight                      | kg | 25                         | 25   | 25                          | 25   |