




# TP6000CE



## Automatic strapping machine

### FEATURES

- Robust and reliable
- Auto strapping, tensioning, sealing and cutting
- Auto standby
- Adjustable sealing time and length depending on product being strapped
- Easy to use: the cycle initiates either by parcel sensor or foot pedal
- After each cycle, the machine resets and sets for the next strapping operation



PP strapping  
(see page 17)



WIDTH OF THE STRAP USED  
TO BE SPECIFIED WHEN ORDERING



**ARCH INTERIOR  
DIMENSIONS: 850 X 600 MM**  
OTHER DIMENSIONS AVAILABLE  
UPON REQUEST, PLEASE CONTACT US



Model		TP6000CE1	TP6000CE3
Strapping width	mm	9/12/15,5	9/12/15,5
Strapping mandrel	mm	Ø 200	Ø 200
Tension force	kg	10 to 70	10 to 70
Number of strapping	min	25	25
Power supply	V	220 single-phase	380 three-phase
Consumption	Kva	0,67	0,67
Cycle speed	s	2,2	2,2
Hauteur table	mm	810	810
Arch dimension (W x H)	mm	850 x 600	850 x 600
Dimensions (L x D x H)	mm	1430 x 620 x 1540	1430 x 620 x 1540
Weight	kg	220	220